

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR M 810, COMP A
M810_A
Revision : 07.07.2006 **Version :** 5.0.0
Print date : 24.07.2006

01. Identification of substance, preparation and company

Product name

CONIPUR M 810, COMP A (250-0810-0) (M810_A)

Manufacturer/Supplier

BASF Construction Chemicals (UK) Ltd

Street/P.O.Box

19 Broadground Road

Country code/Postal code/Town/City

Lakeside, Redditch, Worcestershire, B98 8YP

Telephone / Telefax

+44-161-794-7411 / +44-1527-503576

Emergency information

Schweizer Toxzentrum +0041-1-2515151 (CH)
Centre Anti - Poison +0033 01 40 37 04 04 (FR)
Toxikologické informa-ní st-edisko +00420 224 919 293 (CZ)
Myrkytystietokeskus puh.(suora) +358 (0) 9 471 977 (vaihde) 094711 (FIN)

02. Composition/information on ingredients

Chemical characterization

Polyalcoholic formulation

Hazardous components

DIETHYLMETHYLBENZENEDIAMINE ; EC-No. : 270-877-4 ; CAS-No. : 68479-98-1

Percentage : 2,5 - 10 %

Classification : N ; R 50/53 Xn ; R 48/22 Xn ; R 21/22 Xi ; R 36

For the wording of the listed risk phrases refer to section 16.

03. Hazards identification

Hazard designation

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Classification : N ; R 51/53

04. First-aid measures

After inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration.
Unconsciousness: lateral position - call a physician.

After skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR M 810, COMP A
M810_A
Revision : 07.07.2006 **Version :** 5.0.0
Print date : 24.07.2006

05. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

Waterjet.

Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Special protective equipment

Appropriate breathing apparatus may be required.

Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

06. Accidental release measures

Personal precautions

Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents.

07. Handling and storage

Information for safe handling

Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

Requirements to be met by storerooms and containers

Containers should be kept dry and sealed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.

Storage class (VCI) : 10

08. Exposure controls and personal protection

Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR M 810, COMP A
M810_A
Revision : 07.07.2006 **Version :** 5.0.0
Print date : 24.07.2006

OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

Personal protective equipment

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

Hand protection

Butylrubber $\geq 0,5\text{mm}$ ≥ 480 min. After washing hands replace lost skin fat by fat containing skin creams. By using other gloves with a lower endurance, change them more often.

Eye protection

Use safety glasses.

Body protection

Light protective clothing.

09. Physical and chemical properties

Relevant safety data

Boiling point / range :	(1013 hPa)		no data available		
Flash point :		>	100	°C	DIN 53213
Vapour pressure :	(50 °C)		not applicable		
Density :	(20 °C)	ca.	1,05	g/cm ³	
Solvent-separation test :	(20 °C)		not applicable		
Flow time :	(20 °C)		no data available		DIN-cup 4 mm
Viscosity :	(23 °C)	ca.	1800	mPa.s	

10. Stability and reactivity

Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Exothermic reactions with isocyanates and epoxide resin.

Hazardous decomposition products

Corrosive gases / vapours. Ammonia When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Experience on practice

Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea. The product causes skin corrosions, and it causes serious damage to eyes.

Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

12. Ecological information

Ecotoxic effects

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR M 810, COMP A
M810_A
Revision : 07.07.2006 **Version :** 5.0.0
Print date : 24.07.2006

Aquatic toxicity

Specification : Toxicity to fish (DIETHYLMETHYLBENZENEDIAMINE ; CAS-No. : 68479-98-1)

Parameters : LC 50
Leuciscus idus

Value / dosage : 194 mg/l

Test-period : 48 h

Specification : Toxicity to daphnia (DIETHYLMETHYLBENZENEDIAMINE ; CAS-No. : 68479-98-1)

Parameters : EC50
Species: Daphnia magna Straus 1820

Value / dosage : 0,5 mg/l

Test-period : 48 h

Toxicity to bacteria

Specification : Toxicity to bacteria (DIETHYLMETHYLBENZENEDIAMINE ; CAS-No. : 68479-98-1)

Parameters : EC10
Pseudomonas putida

Value / dosage : 170 mg/l

Test-period : 24 h

Additional ecological information

General ecological information

Do not empty into waters or drains.

13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

Product

Waste key

According to the actual waste legislation it is not possible for us to give the waste code because it depends on the application of the product that we do not know here. If you need some help to determine this code, please ask your executives. Disposal Code according to European Waste Catalog (EWC) please specify according to the use of product, e.g.: 080111* Waste from production, formulation, sales and application of paints and varnishes. Old paints and varnishes, containing organic solvents or some other dangerous product.

14. Transport information

Land transport ADR/RID

Classification

Class :	9	Kemlercode :	90
Substance number :	3082	Classification-Code :	M6

LQ 7

Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazardous components

DIETHYLMETHYLBENZENEDIAMINE

Packaging

Packaging group :	III
Label :	9

Maritime transport IMDG/GGVSea

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR M 810, COMP A
M810_A
Revision : 07.07.2006 **Version :** 5.0.0
Print date : 24.07.2006

Classification

IMDG-Code : 9 **EmS number :** F-A / S-F
UN number : 3082 **Marine Poll. :** -
LQ 5 I

Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazardous components

DIETHYLMETHYLBENZENEDIAMINE

Packaging

Packaging group : III
Label : 9

Air transport ICAO-TI and IATA-DGR

Classification

Class : 9
UN number : 3082

Proper shipping name

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazardous components

DIETHYLMETHYLBENZENEDIAMINE

Packaging

Packaging group : III
Label : 9

15. Regulatory information

Classification according to EC directives

Danger symbol and danger designation



N ; Dangerous for the environment

R-phrases

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

29/35 Do not empty into drains; dispose of this material and its container in a safe way.

61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

National regulatory information

Regulation on inflammable liquids (VbF)

VbF-Class : Not dangerous according to VbF

Water pollution classification

Class : 2 according VwVwS

Other regulations

Please refer to guideline M 004 "Irritant/Corrosive Chemicals" BG Chemie! (DE)

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR M 810, COMP A
M810_A
Revision : 07.07.2006 **Version :** 5.0.0
Print date : 24.07.2006

16. Other information

Further information

We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 16 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

Relevant changes

14. Proper shipping name (ADR) · 14. Proper shipping name (IMDG) · 14. Proper shipping name (ICAO) · 15. S-phrases

R-Phrases of components

21/22	Harmful in contact with skin and if swallowed.
36	Irritating to eyes.
48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Department issuing data sheet

BASF Construction Chemicals Business Line Performance Flooring.

Contact

R. Burgos / C. Schmidt

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
