

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458
Revision : 07.07.2006 **Version :** 6.0.0
Print date : 24.07.2006

01. Identification of substance, preparation and company

Product name

CONIPUR TC 458 (CONIPUR 258) (240-1140-7012) (TC458)

Manufacturer/Supplier

BASF Construction Chemicals (UK) Ltd

Street/P.O.Box

19 Broadground Road, Lakeside

Country code/Postal code/Town/City

Redditch, Worcestershire, B98 8YP

Telephone / Telefax

+44-161-794-7411 / +44-1527-503576

Emergency information

Schweizer Toxzentrum +0041-1-2515151 (CH)
Centre Anti - Poison +0033 01 40 37 04 04 (FR)
Toxikologické informa-ní st-edisko +00420 224 919 293 (CZ)
Myrkytystietokeskus puh.(suora) +358 (0) 9 471 977 (vaihde) 094711 (FIN)

02. Composition/information on ingredients

Chemical characterization

Aliphatic isocyanat prepolymer with slight monomeric parts Contains solvents.

Hazardous components

AROMATIC HYDROCARBON ; EC-No. : 265-199-0 ; CAS-No. : 64742-95-6

Percentage : 10 - 25 %

Classification : R 10 N ; R 51/53 Xn ; R 20 Xn ; R 65

1,2,4-TRIMETHYLBENZENE ; EC-No. : 202-436-9 ; CAS-No. : 95-63-6

Percentage : 2,5 - 10 %

Classification : R 10 N ; R 51/53 Xn ; R 20 Xi ; R 36/37/38

ALIPHATIC POLYISOCYANATE ; CAS-No. : 28182-81-2

Percentage : 2,5 - 10 %

Classification : R 43

PROPYLBENZENE ; EC-No. : 203-132-9 ; CAS-No. : 103-65-1

Percentage : 0,5 - 2,5 %

Classification : R 10 N ; R 51/53 Xn ; R 65 Xi ; R 37

MESITYLENE ; EC-No. : 203-604-4 ; CAS-No. : 108-67-8

Percentage : 0,5 - 2,5 %

Classification : R 10 N ; R 51/53 Xi ; R 37

3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE ; EC-No. : 223-861-6 ; CAS-No. : 4098-71-9

Percentage : 0,1 - 0,5 %

Classification : T ; R 23 N ; R 51/53 R 42/43 Xi ; R 36/37/38

DIBUTYLSTANNANE DILAURATE ; EC-No. : 201-039-8 ; CAS-No. : 77-58-7

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458
Revision : 07.07.2006 **Version :** 6.0.0
Print date : 24.07.2006

Percentage : 0,1 - 0,5 %
Classification : N ; R 50/53 Xn ; R 48/22 Xn ; R 22 Xi ; R 36/38

N-BUTYL-1,2-BENZISOTHIAZOLIN-3-ONE ; CAS-No. : 4299-07-4

Percentage : 0,1 - 0,5 %
Classification : N ; R 50 C ; R 34 R 43 R 53

For the wording of the listed risk phrases refer to section 16.

03. Hazards identification

Hazard designation

Flammable. · Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. · May cause sensitisation by skin contact. · Harmful by inhalation.

Classification : R 10 · N ; R 51/53 · R 43 · Xn ; R 20

04. First-aid measures

After inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

After skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

05. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

Waterjet.

Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. During fires carbon monoxide, nitrogen oxide, isocyanate vapour and traces of hydrogen cyanide may be given off.

Special protective equipment

Appropriate breathing apparatus may be required.

Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

06. Accidental release measures

Personal precautions

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458
Revision : 07.07.2006 **Version :** 6.0.0
Print date : 24.07.2006

Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Subsequently put in the waste container. Do not seal (CO₂ may be given off).

07. Handling and storage

Information for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Provide for fresh air ventilation. Do not inhale the vapour. Avoid contact with skin and eyes. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

Information about protection against explosions and fires

Keep away from ignition sources - No smoking.

Requirements to be met by storerooms and containers

Containers should be kept dry and sealed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Containers should be kept dry and sealed.

Storage class (VCI) : 3A

08. Exposure controls and personal protection

Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Allergics and persons who have problems with the respiration tract are not recommended to work with this product.

Components with critical values that require monitoring at the workplace (exposure limits)

AROMS.-RICH HYDROCARBON-MIXTURE (GERMAN TRGS 900, GROUP 3)

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)
Value : 20 ppm / 100 mg/m³
Category : 4
Version date : 01.09.2003

1,2,4-TRIMETHYLBENZENE ; CAS-No. : 95-63-6

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)
Value : 20 ppm / 100 mg/m³
Category : 2(II)

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458
Revision : 07.07.2006 **Version :** 6.0.0
Print date : 24.07.2006

Remarks : Y
Version date : 01.01.2006
Specification : threshold limit value (EC)
Value : 20 ppm / 100 mg/m³
Version date : 08.06.2000
MESITYLENE ; CAS-No. : 108-67-8
Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)
Value : 20 ppm / 100 mg/m³
Category : 2(II)
Remarks : Y
Version date : 01.01.2006
Specification : threshold limit value (EC)
Value : 20 ppm / 100 mg/m³
Version date : 08.06.2000
3-ISOCYANATOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYL ISOCYANATE ; CAS-No. : 4098-71-9
Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)
Value : 0,005 ppm / 0,046 mg/m³
Category : 1/=2=(I)
Version date : 01.01.2006

Personal protective equipment

Respiratory protection

By spraying: air fed respirator. By other operations than spraying: in well ventilated areas, airfed respirators could be replaced by a combination of charcoal filter and particulate filter mask.

Hand protection

Butylrubber >= 0,5mm >= 480 min. After washing hands replace lost skin fat by fat containing skin creams. By using other gloves with a lower endurance, change them more often.

Eye protection

Use safety glasses.

Body protection

Light protective clothing.

09. Physical and chemical properties

Image

Form : Liquid.
Colour : Coloured.
Odour : Like solvent.

Relevant safety data

Boiling point / range :	(1013 hPa)	no data available
Flash point :	ca.	48 °C DIN 53213
Vapour pressure :	(50 °C) ca.	30 hPa
Density :	(20 °C) ca.	1,3 g/cm ³
Solvent-separation test :	(20 °C) <	3 %
Viscosity :	(23 °C)	1000 mPa.s

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458
Revision : 07.07.2006 **Version :** 6.0.0
Print date : 24.07.2006

Viscosity : (23 °C) 1000 mPa.s

10. Stability and reactivity

Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Exothermic reaction with amines and alcohols. In contact with water (moisture) CO₂ is formed which leads to an excess pressure in closed containers.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Experience on practice

Based on the properties of the isocyanate components and considering toxicological data on similar preparations, this preparation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL (=Occupational Exposure Limit). Repeated exposure may lead to permanent respiratory disability. Delayed reactions possible (breathing problems, coughs, asthma) Inhalation/eye contact: in high concentrations irritating to the mucous membranes, narcotic effect and influence on power of reaction and loss of coordination possible. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

12. Ecological information

Is converted in connection with water in a solid, insoluble and inert polyurea, liberating CO₂.

Ecotoxic effects

Aquatic toxicity

Specification : Toxicity to daphnia (1,2,4-TRIMETHYLBENZENE ; CAS-No. : 95-63-6)

Parameters : EC50
Species: Daphnia magna Straus 1820

Value / dosage : 3600 µg/l

Test-period : 48 h

Specification : Toxicity to fish (MESITYLENE ; CAS-No. : 108-67-8)

Parameters : LC 50
Carassius auratus

Value / dosage : 20,6 mg/l

Test-period : 24 h

Specification : Toxicity to daphnia (MESITYLENE ; CAS-No. : 108-67-8)

Parameters : EC50
Species: Daphnia magna Straus 1820

Value / dosage : 50 mg/l

Test-period : 24 h

Specification : Toxicity to daphnia (MESITYLENE ; CAS-No. : 108-67-8)

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458
Revision : 07.07.2006 **Version :** 6.0.0
Print date : 24.07.2006

Parameters : NOEC
Species: Daphnia magna Straus 1820
Value / dosage : 400 µg/l
Test-period : 504 h
Specification : Toxicity to algae (MESITYLENE ; CAS-No. : 108-67-8)
Parameters : EC50
Scenedesmus subspicatus
Value / dosage : 40 µg/l
Test-period : 48 h

Additional ecological information

General ecological information

Do not empty into waters or drains.

13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

Product

Recommendation

In accordance with local official regulations. Pass on to an appropriate incinerating plant or depository or recycling.

Waste key

According to the actual waste legislation it is not possible for us to give the waste code because it depends on the application of the product that we do not know here. If you need some help to determine this code, please ask your executives. Disposal Code according to European Waste Catalog (EWC) please specify according to the use of product, e.g.: 080111* Waste from production, formulation, sales and application of paints and varnishes. Old paints and varnishes, containing organic solvents or some other dangerous product.

14. Transport information

Land transport ADR/RID

Classification

Class : 3 **Kemlercode :** 30
Substance number : 1866 **Classification-Code :** F1

ADR : - (<= 450 l) · Special provisions : 640E · LQ 7

Proper shipping name

RESIN SOLUTION

Packaging

Packaging group : III
Label : 3

Maritime transport IMDG/GGVSea

Classification

IMDG-Code : 3 **EmS number :** F-E / S-E
UN number : 1866 **Marine Poll. :** P

IMDG 2.3.2.5 (<= 30 l) · LQ 5 I

Proper shipping name

RESIN SOLUTION

Packaging

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458
Revision : 07.07.2006 **Version :** 6.0.0
Print date : 24.07.2006

Packaging group : III
Label : 3

Air transport ICAO-TI and IATA-DGR

Classification

Class : 3
UN number : 1866

Proper shipping name

RESIN SOLUTION

Packaging

Packaging group : III
Label : 3

15. Regulatory information

Classification according to EC directives

Danger symbol and danger designation



Xn ; Harmful



N ; Dangerous for the environment

Hazard-determining components of labelling

ALIPHATIC POLYISOCYANATE ; CAS-No. : 28182-81-2

R-phrases

10 Flammable.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
43 May cause sensitisation by skin contact.
20 Harmful by inhalation.

S-phrases

29/35 Do not empty into drains; dispose of this material and its container in a safe way.
61 Avoid release to the environment. Refer to special instructions/Safety data sheets.
2 Keep out of the reach of children.
51 Use only in well-ventilated areas.
37 Wear suitable gloves.
46 If swallowed, seek medical advice immediately and show this container or label.
24 Avoid contact with skin.

Special designation for certain preparations

91 Contains isocyanates. See information provided by the manufacturer.

National regulatory information

Regulation on inflammable liquids (VbF)

VbF-Class : Not dangerous according to VbF

Emission control act ("TA-Luft")

Sum organic substances class I : < 5 %

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458
Revision : 07.07.2006 **Version :** 6.0.0
Print date : 24.07.2006

Sum organic substances class III : 10 - 15 %
Sum cancerogen substances class III : < 1 %

Water pollution classification

Class : 2 according VwVwS

Other regulations

Observe UVV for handling of painting material (VBG 23). See also "recommendations for the handling of aromatic isocyanates". (BG-chemistry MO44).

16. Other information

Restrictions on use recommended by the manufacturer

Coating material - use only according to the Technical Information of the product.

Further information

We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 16 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

Relevant changes

02. Hazardous components · 08. Components with critical values that require monitoring at the workplace (exposure limits) · 14. Proper shipping name (ADR) · 14. Substance releasing the danger (ADR) · 14. Proper shipping name (IMDG) · 14. Substance releasing the danger (IMDG) · 14. Proper shipping name (ICAO) · 14. Substance releasing the danger (ICAO) · 15. S-phrases

R-Phrases of components

10	Flammable.
20	Harmful by inhalation.
22	Harmful if swallowed.
23	Toxic by inhalation.
34	Causes burns.
36/37/38	Irritating to eyes, respiratory system and skin.
36/38	Irritating to eyes and skin.
37	Irritating to respiratory system.
42/43	May cause sensitisation by inhalation and skin contact.
43	May cause sensitisation by skin contact.
48/22	Harmful: danger of serious damage to health by prolonged exposure if swallowed.
50	Very toxic to aquatic organisms.
50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
53	May cause long-term adverse effects in the aquatic environment.
65	Harmful: may cause lung damage if swallowed.

Department issuing data sheet

BASF Construction Chemicals Business Line Performance Flooring.

Contact

R. Burgos / C. Schmidt

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Material Safety Data Sheet

according to 91/155/EEC

Product name : CONIPUR TC 458 (CONIPUR 258)
TC458

Revision : 07.07.2006 **Version :** 6.0.0

Print date : 24.07.2006
