

Emaco CP Anode Overlay Part 1



Irritant

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

PRODUCT NAME: Emaco CP Anode Overlay Part 1

PART No.:

SUPPLIER: BASF Construction Chemicals (UK) Ltd
Albany House
Swinton Hall Road
Swinton Manchester M27 4DT

TEL: (+44) 161 794 7411

FAX: (+44) 161 727 8547

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characteristics Sand, cement, dry powder.

Hazardous components

Portland cement (Cr-VI < or = 2 ppm) Conc: 20 - 70 % - Einescs: 266-043-4 - CAS: 65997-15-1 - Xi - R36/37/38, R41

3. HAZARDS IDENTIFICATION

Risks R36/37/38 - Irritating to eyes, respiratory system and skin.
R41 - Risk of serious damage to eyes.

4. FIRST AID MEASURES

Eye contact Rinse immediately with plenty of water for at least 15 minutes. Get medical attention if irritation persists.

Skin contact Remove and wash contaminated clothes. Wash off immediately with soap and plenty of water. Get medical attention if irritation persists.

Inhalation Remove affected person to fresh air. In case of breathing difficulty or distress, get medical attention.

Ingestion If accidentally swallowed drink plenty of water and obtain medical attention. Point out the high alkalinity of cement.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Water spray, foam, carbon dioxide, dry powder

Extinguishing media which must not be used for safety reasons Water jet

Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases None known

Protective equipment Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Avoid contact with skin and eyes.
Avoid inhalation of dust.

Environmental precautions Do not discharge into drains and sewers because of high alkalinity.

Emaco CP Anode Overlay Part 1

Methods for cleaning up

Collect in a container and re-use. Soak up with sand or other suitable material and dispose as per 13.

7. HANDLING AND STORAGE

Handling

Avoid dust formation. Do not inhale dust.

Avoid spilling, skin and eye contact. Observe industrial safety and hygiene practice.

Storage

Keep packaging tightly closed.

Store in a cool, dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits values

Exposure controls :

Occupational exposure controls

Environmental exposure controls

Provide adequate ventilation or air evacuation at workplace.

Personal protection :

Respiratory protection

dust mask

Hand protection

rubber gloves

Eye protection

goggles or face shield

Skin and body protection

apron or light protective clothing

Wash hands before breaks and after finishing work.

Do not eat, drink or smoke at workplace.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form

powder

Colour

grey

Odour

characteristic

Density

not applicable

Bulk density

not applicable

pH

> 11 at 20 °C

Flash point

not applicable

Autoignition temperature

not applicable

Vapour pressure

not applicable

Water solubility

miscible

Viscosity

not applicable

Explosion limits :

- upper

not applicable

- lower

not applicable

Decomposition temperature

not applicable

Boiling point/range

not applicable

Other data

Mixing with water results in an alkaline suspension. Simultaneous hardening with emission of hydration heat occurs.

10. STABILITY AND REACTIVITY

Conditions to avoid

wet and humid areas.

Materials to avoid

Exothermic reaction with strong acids

Hazardous decomposition products

None, under application conditions.

Emaco CP Anode Overlay Part 1

11. TOXICOLOGICAL INFORMATION

Acute toxicity :

LD50 oral rat	not determined
LD50 dermal rat	not determined
LD50 dermal rabbit	not determined
LC50 inhalation rat	not determined

Acute effects/symptoms :

After eye contact	Irritating to eyes.
After skin contact	Irritating to skin.
After inhalation	Inhalation of cement dust may cause irritation of the respiratory tracts.
After ingestion	

Chronic effects

May cause sensitisation by inhalation and skin contact.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Do not discharge into drains and sewers because of high alkalinity. Due to its alkalinity, this product is harmful to fish and other aquatic life forms.

13. DISPOSAL CONSIDERATIONS

Product

Re-use where possible. Dispose according to local regulations for construction materials.

Packaging

Dispose according to local regulations.

14. TRANSPORT INFORMATION

General

This product is not classified as dangerous in the meaning of transport regulations.

Road transport - ADR

Railway transport - RID

Sea transport - IMDG

Air transport - ICAO/IATA

15. REGULATORY INFORMATION

Labelling

Xi - Irritant

R-phrase(s)

R36/37/38 - Irritating to eyes, respiratory system and skin.

R41 - Risk of serious damage to eyes.

S-phrase(s)

S 2 - Keep out of reach of children.

S22 - Do not breathe dust.

S24/25 - Avoid contact with skin and eyes.

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39 - Wear suitable protective clothing, gloves, and eye/face protection.

S46 - If swallowed, seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

Further information

None

Emaco CP Anode Overlay Part 1

Relevant changes

R-phrases of components

R36/37/38 - Irritating to eyes, respiratory system and skin.

R41 - Risk of serious damage to eyes.

Important Note

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.
