

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

01. Identification of substance, preparation and company

Product name

MASTERTOP P 684 (CONIPUR 84) (820-0001-1167) (84)

Manufacturer/Supplier

BASF Construction Chemicals

Street/P.O.Box

19 Broad Ground Road, Lakeside

Country code/Postal code/Town/City

Redditch, Worcestershire B98 8YP

Telephone / Telefax

+44(0)161 794 7411 / +44(0)1527 503576

Emergency information

Schweizer Toxzentrum +0041-1-2515151 (CH)
Centre Anti - Poison +0033 01 40 37 04 04 (FR)
Toxikologické informa-ní st-edisko +00420 224 919 293 (CZ)
Myrkytystietokeskus puh.(suora) +358 (0) 9 471 977 (vaihde) 094711 (FIN)

02. Composition/information on ingredients

Chemical characterization

Polyvinylbutyral - adhesive primer

Hazardous components

BUTAN-1-OL ; EC-No. : 200-751-6 ; CAS-No. : 71-36-3

Percentage : 25 - 50 %

Classification : R 10 Xi ; R 41 Xn ; R 22 Xi ; R 37/38 R 67

XYLENE ; EC-No. : 215-535-7 ; CAS-No. : 1330-20-7

Percentage : 10 - 25 %

Classification : R 10 Xn ; R 20/21 Xi ; R 38

ETHYLBENZENE ; EC-No. : 202-849-4 ; CAS-No. : 100-41-4

Percentage : 2,5 - 10 %

Classification : F ; R 11 Xn ; R 20

N-BUTYL ACETATE ; EC-No. : 204-658-1 ; CAS-No. : 123-86-4

Percentage : 0,5 - 2,5 %

Classification : R 10 R 67 R 66

2-METHYLPROPAN-1-OL ; EC-No. : 201-148-0 ; CAS-No. : 78-83-1

Percentage : 0,5 - 2,5 %

Classification : R 10 Xi ; R 41 Xi ; R 37/38 R 67

PHENOL ; EC-No. : 203-632-7 ; CAS-No. : 108-95-2

Percentage : 0,1 - 0,5 %

Classification : T ; R 23/24/25 C ; R 34 Muta. Cat.3 ; R 68 Xn ; R 48/20/21/22

For the wording of the listed risk phrases refer to section 16.

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

03. Hazards identification

Hazard designation

Flammable. · Risk of serious damage to eyes. · Harmful by inhalation, in contact with skin and if swallowed.
Classification : R 10 · Xi ; R 41 · Xn ; R 20/21/22 · Xi ; R 37/38

04. First-aid measures

After inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration.
Unconsciousness: lateral position - call a physician.

After skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

05. Fire-fighting measures

Suitable extinguishing media

Alcohol resistant foam, CO₂, powders, water spray.

Unsuitable extinguishing media

Waterjet.

Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. During fires carbon monoxide, nitrogen oxide, isocyanate vapour and traces of hydrogen cyanide may be given off.

Special protective equipment

Appropriate breathing apparatus may be required.

Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

06. Accidental release measures

Personal precautions

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Subsequently put in the waste container. Do not seal (CO₂ may be given off).

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

07. Handling and storage

Information for safe handling

Prevent the creation of inflammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the OEL (=Occupational Exposure Limit). Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Provide for fresh air ventilation. Do not inhale the vapour. Avoid contact with skin and eyes. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

Information about protection against explosions and fires

Keep away from ignition sources - No smoking.

Requirements to be met by storerooms and containers

Containers should be kept dry and sealed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Containers should be kept dry and sealed.

Storage class (VCI) : 3A

08. Exposure controls and personal protection

Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Allergics and persons who have problems with the respiration tract are not recommended to work with this product.

Components with critical values that require monitoring at the workplace (exposure limits)

BUTAN-1-OL ; CAS-No. : 71-36-3

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)
Value : 100 ppm / 310 mg/m³
Category : 1(I)
Remarks : Y
Version date : 01.01.2006

Specification : TRGS 903 - biological maximum limits (D)
Parameter : 1-Butanol / urine / before the next shift
Value : 2 mg/g Kr
Version date : 31.03.2004

Specification : TRGS 903 - biological maximum limits (D)
Parameter : 1-Butanol / urine / end of exposure or shift
Value : 10 mg/g Kr
Version date : 31.03.2004

XYLENE ; CAS-No. : 1330-20-7

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

Value : 100 ppm / 440 mg/m³
Category : 2(II)
Remarks : H
Version date : 01.01.2006
Specification : TRGS 903 - biological maximum limits (D)
Parameter : Xylene / whole blood / end of exposure or shift
Value : 1,5 mg/l
Version date : 31.03.2004
Specification : TRGS 903 - biological maximum limits (D)
Parameter : Methylhippuric acid / urine / end of exposure or shift
Value : 2 g/l
Version date : 31.03.2004
Specification : Short term exposure limit (EC)
Value : 100 ppm / 442 mg/m³
Remarks : H
Version date : 08.06.2000
Specification : threshold limit value (EC)
Value : 50 ppm / 221 mg/m³
Remarks : H
Version date : 08.06.2000
ETHYLBENZENE ; CAS-No. : 100-41-4
Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)
Value : 100 ppm / 440 mg/m³
Category : 2(I)
Remarks : H
Version date : 01.01.2006
Specification : TRGS 903 - biological maximum limits (D)
Parameter : Ethylbenzene/ whole blood / end of exposure or shift
Value : 1 mg/l
Version date : 31.03.2004
Specification : TRGS 903 - biological maximum limits (D)
Parameter : Mandelic acid + Phenylglyoxyl acid / urine / end of exposure or shift
Value : 800 mg/g Kr
Version date : 31.03.2004
Specification : Short term exposure limit (EC)
Value : 200 ppm / 884 mg/m³
Remarks : H
Version date : 08.06.2000
Specification : threshold limit value (EC)
Value : 100 ppm / 442 mg/m³
Remarks : H
Version date : 08.06.2000
2-METHYLPROPAN-1-OL ; CAS-No. : 78-83-1

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)
Value : 100 ppm / 310 mg/m³
Category : 1(I)
Remarks : Y
Version date : 01.01.2006

PHENOL ; CAS-No. : 108-95-2

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace (D)
Value : 2 ppm / 7,8 mg/m³
Remarks : H
Version date : 01.01.2006

Specification : TRGS 903 - biological maximum limits (D)
Parameter : Phenol / urine / end of exposure or shift
Value : 300 mg/l
Version date : 31.03.2004

Specification : threshold limit value (EC)
Value : 2 ppm / 7,8 mg/m³
Remarks : H
Version date : 08.06.2000

Personal protective equipment

Respiratory protection

By spraying: air fed respirator. By other operations than spraying: in well ventilated areas, airfed respirators could be replaced by a combination of charcoal filter and particulate filter mask.

Hand protection

Butylrubber >= 0,5mm >= 480 min. After washing hands replace lost skin fat by fat containing skin creams. By using other gloves with a lower endurance, change them more often.

Eye protection

Use safety glasses.

Body protection

Light protective clothing.

09. Physical and chemical properties

Image

Form : Liquid.
Colour : Green-yellowish.
Odour : Like solvent.

Relevant safety data

Boiling point / range :	(1013 hPa)	ca.	82 °C	
Flash point :		>	23 °C	DIN 53213
Vapour pressure :	(50 °C)	ca.	5 hPa	
Density :	(20 °C)	ca.	0,9 g/cm ³	
Solvent-separation test :	(20 °C)	<	3 %	
Viscosity :	(23 °C)		120 mPa.s	

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

10. Stability and reactivity

Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Exothermic reaction with amines and alcohols. In contact with water (moisture) CO₂ is formed which leads to an excess pressure in closed containers.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Experience on practice

Based on the properties of the isocyanate components and considering toxicological data on similar preparations, this preparation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL (=Occupational Exposure Limit). Repeated exposure may lead to permanent respiratory disability. Delayed reactions possible (breathing problems, coughs, asthma) Inhalation/eye contact: in high concentrations irritating to the mucous membranes, narcotic effect and influence on power of reaction and loss of coordination possible. Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.

Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

12. Ecological information

Is converted in connection with water in a solid, insoluble and inert polyurea, liberating CO₂.

Ecotoxicological effects

Aquatic toxicity

Specification :	Toxicity to fish (XYLENE ; CAS-No. : 1330-20-7)
Parameters :	LC 50 Species: Trout
Value / dosage :	3,77 mg/l
Test-period :	96 h
Specification :	Toxicity to daphnia (XYLENE ; CAS-No. : 1330-20-7)
Parameters :	EC50 Species: Daphnia magna Straus 1820
Value / dosage :	7,4 mg/l
Test-period :	48 h
Specification :	Toxicity to fish (PHENOL ; CAS-No. : 108-95-2)
Parameters :	LC 50 Brachydanio rerio
Value / dosage :	27,8 mg/l
Test-period :	96 h
Specification :	Toxicity to fish (PHENOL ; CAS-No. : 108-95-2)
Parameters :	LC0 Brachydanio rerio
Value / dosage :	222 mg/l

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

Test-period : 99 h
Specification : Toxicity to daphnia (PHENOL ; CAS-No. : 108-95-2)
Parameters : EC50
Species: Daphnia magna Straus 1820
Value / dosage : 6,6 mg/l
Test-period : 48 h

Additional ecological information

General ecological information

Do not empty into waters or drains.

13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

Product

Recommendation

In accordance with local official regulations. Pass on to an appropriate incinerating plant or depository or recycling.

Waste key

According to the actual waste legislation it is not possible for us to give the waste code because it depends on the application of the product that we do not know here. If you need some help to determine this code, please ask your executives. Disposal Code according to European Waste Catalog (EWC) please specify according to the use of product, e.g.: 080111* Waste from production, formulation, sales and application of paints and varnishes. Old paints and varnishes, containing organic solvents or some other dangerous product.

14. Transport information

Land transport ADR/RID

Classification

Class : 3 **Kemlercode :** 30
Substance number : 1263 **Classification-Code :** F1

Special provisions : 640E · LQ 7

Proper shipping name

PAINT

Packaging

Packaging group : III
Label : 3

Maritime transport IMDG/GGVSea

Classification

IMDG-Code : 3 **EmS number :** F-E / S-E
UN number : 1263 **Marine Poll. :** -

LQ 5 I

Proper shipping name

PAINT

Packaging

Packaging group : III
Label : 3

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

Air transport ICAO-TI and IATA-DGR

Classification

Class : 3
UN number : 1263

Proper shipping name

PAINT

Packaging

Packaging group : III
Label : 3

15. Regulatory information

Classification according to EC directives

Danger symbol and danger designation



Xn ; Harmful

Hazard-determining components of labelling

BUTAN-1-OL ; CAS-No. : 71-36-3

XYLENE ; CAS-No. : 1330-20-7

R-phrases

10 Flammable.
41 Risk of serious damage to eyes.
20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
37/38 Irritating to respiratory system and skin.

S-phrases

2 Keep out of the reach of children.
35 This material and its container must be disposed of in a safe way.
51 Use only in well-ventilated areas.
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.
64 If swallowed, rinse mouth with water (only if the person is conscious).
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
7/9 Keep container tightly closed and in a well-ventilated place.
25 Avoid contact with eyes.

National regulatory information

Germany: Safety Instruction Code of German occupational safety and health organisation. Berufsgenossenschaften der Bauwirtschaft: GISCODE PU 50

Regulation on inflammable liquids (VbF)

VbF-Class : AII

Emission control act ("TA-Luft")

Sum organic substances class I : < 5 %

Water pollution classification

Class : 2 according VwVwS

Other regulations

Material Safety Data Sheet

according to 91/155/EEC

Product name : MASTERTOP P 684 (CONIPUR 84)
84
Revision : 07.07.2006 **Version :** 7.0.0
Print date : 24.07.2006

Observe UVV for handling of painting material (VBG 23). See also "recommendations for the handling of aromatic isocyanates". (BG-chemistry MO44).

16. Other information

Restrictions on use recommended by the manufacturer

Coating material - use only according to the Technical Information of the product.

Further information

We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 16 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

Relevant changes

08. Components with critical values that require monitoring at the workplace (exposure limits) · 14. Proper shipping name (ADR) · 14. Proper shipping name (IMDG) · 14. Proper shipping name (ICAO) · 15. S-phrases

R-Phrases of components

10	Flammable.
11	Highly flammable.
20	Harmful by inhalation.
20/21	Harmful by inhalation and in contact with skin.
22	Harmful if swallowed.
23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
34	Causes burns.
37/38	Irritating to respiratory system and skin.
38	Irritating to skin.
41	Risk of serious damage to eyes.
48/20/21/22	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
66	Repeated exposure may cause skin dryness or cracking.
67	Vapours may cause drowsiness and dizziness.
68	Possible risk of irreversible effects.

Department issuing data sheet

BASF Construction Chemicals Business Line Performance Flooring.

Contact

R. Burgos / C. Schmidt

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
