

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP TC 441 P (C), COMP A (CONIPUR 41)  
41\_A  
**Revision :** 07.07.2006      **Version :** 12.0.0  
**Print date :** 24.07.2006

---

## 01. Identification of substance, preparation and company

### Product name

MASTERTOP TC 441 P (C), COMP A (CONIPUR 41) (310-2003-7030) (41\_A)

### Manufacturer/Supplier

BASF Construction Chemicals (UK) Ltd

### Street/P.O.Box

19 Broadground Road, Lakeside

### Country code/Postal code/Town/City

Redditch, Worcestershire, B98 8YP

### Telephone / Telefax

+44-161-794-74112525 / +44-1527-503576

### Emergency information

Schweizer Toxzentrum +0041-1-2515151 (CH)  
Centre Anti - Poison +0033 01 40 37 04 04 (FR)  
Toxikologické informa-ní st-edisko +00420 224 919 293 (CZ)  
Myrkytystietokeskus puh.(suora) +358 (0) 9 471 977 (vaihde) 094711 (FIN)

---

## 02. Composition/information on ingredients

### Chemical characterization

Aliphatic polyisocyanates

### Hazardous components

ALIPHATIC POLYISOCYANATE ; CAS-No. : 28182-81-2

Percentage : 50 - 100 %

Classification : R 43 R 52/53

PHENOL, 2-(2H-BENZOTRIAZOL-2-YL)-6-DODECYL-4-METHYL ; EC-No. : 401-680-5 ; CAS-No. : 23328-53-2

Percentage : 0,5 - 2,5 %

Classification : N ; R 51/53

AROMATIC HYDROCARBON ; EC-No. : 265-199-0 ; CAS-No. : 64742-95-6

Percentage : 0,1 - 0,5 %

Classification : R 10 N ; R 51/53 Xn ; R 20 Xn ; R 65

HEXAMETHYLENE-DI-ISOCYANATE ; EC-No. : 212-485-8 ; CAS-No. : 822-06-0

Percentage : 0,1 - 0,5 %

Classification : T ; R 23 R 42/43 Xi ; R 36/37/38

1,2,4-TRIMETHYLBENZENE ; EC-No. : 202-436-9 ; CAS-No. : 95-63-6

Percentage : 0,1 - 0,5 %

Classification : R 10 N ; R 51/53 Xn ; R 20 Xi ; R 36/37/38

For the wording of the listed risk phrases refer to section 16.

---

## 03. Hazards identification

### Hazard designation

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP TC 441 P (C), COMP A (CONIPUR 41)  
41\_A  
**Revision :** 07.07.2006      **Version :** 12.0.0  
**Print date :** 24.07.2006

---

May cause sensitisation by skin contact. · Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Classification : R 43 · R 52/53

---

## 04. First-aid measures

### **After inhalation**

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration. Unconsciousness: lateral position - call a physician.

### **After skin contact**

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

### **After eye contact**

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

### **After ingestion**

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

---

## 05. Fire-fighting measures

### **Suitable extinguishing media**

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray.

### **Unsuitable extinguishing media**

Waterjet.

### **Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged**

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. During fires carbon monoxide, nitrogen oxide, isocyanate vapour and traces of hydrogen cyanide may be given off.

### **Special protective equipment**

Appropriate breathing apparatus may be required.

### **Additional information**

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

---

## 06. Accidental release measures

### **Personal precautions**

Remove ignition sources. Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

### **Environmental precautions**

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

### **Methods for cleaning up/collecting**

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Subsequently put in the waste container. Do not seal (CO<sub>2</sub> may be given off).

---

## 07. Handling and storage

### **Information for safe handling**

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP TC 441 P (C), COMP A (CONIPUR 41)  
41\_A  
**Revision :** 07.07.2006      **Version :** 12.0.0  
**Print date :** 24.07.2006

---

Provide for fresh air ventilation. Do not inhale the vapour. Avoid contact with skin and eyes. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

## Information about protection against explosions and fires

No particular measures required.

## Requirements to be met by storerooms and containers

Containers should be kept dry and sealed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

## Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

## Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Containers should be kept dry and sealed. Avoid heating over 50°C. Avoid cooling to under 0°C.

**Storage class (VCI) :** 10

---

## 08. Exposure controls and personal protection

### Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn. Allergics and persons who have problems with the respiration tract are not recommended to work with this product.

### Components with critical values that require monitoring at the workplace (exposure limits)

HEXAMETHYLENE-DI-ISOCYANATE ; CAS-No. : 822-06-0

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace ( D )  
Value : 0,005 ppm / 0,035 mg/m<sup>3</sup>  
Category : 1/=2=(I)  
Version date : 01.01.2006

1,2,4-TRIMETHYLBENZENE ; CAS-No. : 95-63-6

Specification : TRGS 900 - maximum limit in the atmosphere at the workplace ( D )  
Value : 20 ppm / 100 mg/m<sup>3</sup>  
Category : 2(II)  
Remarks : Y  
Version date : 01.01.2006

### Personal protective equipment

#### Respiratory protection

By spraying: air fed respirator. By other operations than spraying: in well ventilated areas, airfed respirators could be replaced by a combination of charcoal filter and particulate filter mask.

#### Hand protection

Butylrubber >= 0,5mm >= 480 min. After washing hands replace lost skin fat by fat containing skin creams. By using other gloves with a lower endurance, change them more often.

#### Eye protection

Use safety glasses.

#### Body protection

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP TC 441 P (C), COMP A (CONIPUR 41)  
41\_A  
**Revision :** 07.07.2006      **Version :** 12.0.0  
**Print date :** 24.07.2006

---

Light protective clothing.

---

## 09. Physical and chemical properties

### Image

**Form :** Liquid.  
**Colour :** Coloured.  
**Odour :** Poor, characteristic.

### Relevant safety data

<b>Boiling point / range :</b>	( 1013 hPa )		no data available		
<b>Flash point :</b>		>	100	°C	DIN 53213
<b>Vapour pressure :</b>	( 50 °C )		no data available		
<b>Density :</b>	( 20 °C )	ca.	1,5	g/cm <sup>3</sup>	
<b>Solvent-separation test :</b>	( 20 °C )		inapplicable		
<b>Viscosity :</b>	( 20 °C )		3000	mPa.s	

---

## 10. Stability and reactivity

### Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Exothermic reaction with amines and alcohols. In contact with water (moisture) CO<sub>2</sub> is formed which leads to an excess pressure in closed containers.

### Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

---

## 11. Toxicological information

### Experience on practice

Based on the properties of the isocyanate components and considering toxicological data on similar preparations, this preparation may cause acute irritation and/or sensitization of the respiratory system leading to an asthmatic condition, wheeziness and a tightness of the chest. Sensitized persons may subsequently show asthmatic symptoms when exposed to atmospheric concentrations well below the OEL (=Occupational Exposure Limit). Repeated exposure may lead to permanent respiratory disability. Delayed reactions possible (breathing problems, coughs, asthma)

### Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

---

## 12. Ecological information

Is converted in connection with water in a solid, insoluble and inert polyurea, liberating CO<sub>2</sub>.

### Ecotoxicological effects

#### Aquatic toxicity

Specification : Toxicity to daphnia ( 1,2,4-TRIMETHYLBENZENE ; CAS-No. : 95-63-6 )  
Parameters : EC50  
Species: Daphnia magna Straus 1820

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP TC 441 P (C), COMP A (CONIPUR 41)  
41\_A  
**Revision :** 07.07.2006      **Version :** 12.0.0  
**Print date :** 24.07.2006

---

Value / dosage : 3600 µg/l  
Test-period : 48 h

## Additional ecological information

### General ecological information

Do not empty into waters or drains.

---

## 13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

### Product

#### Recommendation

In accordance with local official regulations. Pass on to an appropriate incinerating plant or depository or recycling.

#### Waste key

According to the actual waste legislation it is not possible for us to give the waste code because it depends on the application of the product that we do not know here. If you need some help to determine this code, please ask your executives. Disposal Code according to European Waste Catalog (EWC) please specify according to the use of product, e.g.: 080111\* Waste from production, formulation, sales and application of paints and varnishes. Old paints and varnishes, containing organic solvents or some other dangerous product.

---

## 14. Transport information

### Land transport ADR/RID

#### Classification

Class : -

### Maritime transport IMDG/GGVSea

#### Classification

IMDG-Code : -

### Air transport ICAO-TI and IATA-DGR

#### Classification

Class : -

---

## 15. Regulatory information

### Classification according to EC directives

#### Danger symbol and danger designation



Xi ; Irritant

#### Hazard-determining components of labelling

ALIPHATIC POLYISOCYANATE ; CAS-No. : 28182-81-2

#### R-phrases

43                                      May cause sensitisation by skin contact.  
52/53                                     Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### S-phrases

61                                         Avoid release to the environment. Refer to special instructions/Safety data sheets.

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP TC 441 P (C), COMP A (CONIPUR 41)  
41\_A  
**Revision :** 07.07.2006      **Version :** 12.0.0  
**Print date :** 24.07.2006

---

- 2                      Keep out of the reach of children.
- 35                     This material and its container must be disposed of in a safe way.
- 37                     Wear suitable gloves.
- 24                     Avoid contact with skin.

#### Special designation for certain preparations

- 91                     Contains isocyanates. See information provided by the manufacturer.

#### National regulatory information

Germany: Safety Instruction Code of german occupational safety and health organisation. Berufsgenossenschaften der Bauwirtschaft: GISCODE PU 50

#### Regulation on inflammable liquids (VbF)

VbF-Class : Not dangerous according to VbF

#### Emission control act ("TA-Luft")

- Sum organic substances class I : < 5 %
- Sum organic substances class III : < 5 %
- Sum cancerogen substances class III : < 1 %

#### Water pollution classification

Class : 1 according VwVwS

#### Other regulations

Observe UVV for handling of painting material (VBG 23). See also "recommendations for the handling of aromatic isocyanates". (BG-chemistry MO44).  
Switzerland: Please refer to the guidelines of SUVA and EKAS. e.g.: "Guidline for preventing accidents when using two component resins" (SUVA 1854)

#### International regulatory information

Denmark: PR-Nr. : 661184 MAL-Code: 5-3 MAL-Code for ready mixture: 0-3

---

## 16. Other information

### Processing instructions / technical data sheets

Coating material - use only according to the Technical Information of the product.

### Further information

We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 16 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

#### Relevant changes

- 02. Hazardous components · 08. Components with critical values that require monitoring at the workplace (exposure limits) ·
- 15. Water pollution classification

#### R-Phrases of components

- 10                     Flammable.
- 20                     Harmful by inhalation.
- 23                     Toxic by inhalation.
- 36/37/38             Irritating to eyes, respiratory system and skin.
- 42/43                 May cause sensitisation by inhalation and skin contact.
- 43                     May cause sensitisation by skin contact.
- 51/53                 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 52/53                 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

