

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP P 605, COMP B (CONIPOX 605)  
605\_B  
**Revision :** 07.07.2006      **Version :** 6.0.0  
**Print date :** 24.07.2006

---

## 01. Identification of substance, preparation and company

### Product name

MASTERTOP P 605, COMP B (CONIPOX 605) (630-0605-5299) (605\_B)

### Manufacturer/Supplier

BASF Construction Chemicals  
(Schweiz) AG Division CONICA Technik

### Street/P.O.Box

Industriestrasse 26 /

### Country code/Postal code/Town/City

CH-8207 Schaffhausen

### Telephone / Telefax

+41-58-958-2525 / +41-58-958-3525

### Emergency information

Schweizer Toxzentrum +0041-1-2515151 (CH)  
Centre Anti - Poison +0033 01 40 37 04 04 (FR)  
Toxikologické informa-ní st-edisko +00420 224 919 293 (CZ)  
Myrkytystietokeskus puh.(suora) +358 (0) 9 471 977 (vaihde) 094711 (FIN)

---

## 02. Composition/information on ingredients

### Chemical characterization

Modified cycloaliphatic polyamine mixture

### Hazardous components

BENZYL ALCOHOL ; EC-No. : 202-859-9 ; CAS-No. : 100-51-6

Percentage : 10 - 25 %

Classification : Xn ; R 20/22

M-PHENYLENEBIS(METHYLAMINE) ; EC-No. : 216-032-5 ; CAS-No. : 1477-55-0

Percentage : 10 - 25 %

Classification : C ; R 34 Xn ; R 20/21/22

CYCLOHEX-1,2-YLENEDIAMINE ; EC-No. : 211-776-7 ; CAS-No. : 694-83-7

Percentage : 10 - 25 %

Classification : C ; R 34 R 43

3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; EC-No. : 220-666-8 ; CAS-No. : 2855-13-2

Percentage : 2,5 - 10 %

Classification : C ; R 34 R 43 R 52/53 Xn ; R 21/22

POLYOXYPROPYLEN DIAMINE ; CAS-No. : 9046-10-0

Percentage : 2,5 - 10 %

Classification : C ; R 34 Xn ; R 21/22

2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL ; EC-No. : 202-013-9 ; CAS-No. : 90-72-2

Percentage : 2,5 - 10 %

Classification : Xn ; R 22 Xi ; R 36/38

2-METHYL-1,5-PENTAMETHYLENDIAMINE ; EC-No. : 239-556-6 ; CAS-No. : 15520-10-2

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP P 605, COMP B (CONIPOX 605)  
605\_B  
**Revision :** 07.07.2006      **Version :** 6.0.0  
**Print date :** 24.07.2006

---

Percentage : 0,5 - 2,5 %  
Classification : C ; R 34 · Xn ; R 20/22

For the wording of the listed risk phrases refer to section 16.

---

## 03. Hazards identification

### Hazard designation

Causes burns. · May cause sensitisation by skin contact. · Harmful by inhalation, in contact with skin and if swallowed.

Classification : C ; R 34 · R 43 · Xn ; R 20/21/22

### Additional information

Danger of irritation to eyes, nose, throat and the air passages.

---

## 04. First-aid measures

### After inhalation

Take the casualty into the fresh air and keep warm. Keep at rest. Irregular breathing/no breathing: artificial respiration.  
Unconsciousness: lateral position - call a physician.

### After skin contact

Immediately remove all contaminated clothing. Wash away with soap and water and rinse. Do NOT use solvents or thinners.

### After eye contact

Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician.

### After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

---

## 05. Fire-fighting measures

### Suitable extinguishing media

Alcohol resistant foam, CO<sub>2</sub>, powders, water spray.

### Unsuitable extinguishing media

Waterjet.

### Special risk posed by the substance or by the actual preparation, its combustion products or gases discharged

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

### Special protective equipment

Appropriate breathing apparatus may be required.

### Additional information

Cool endangered containers with water in case of fire. Do not allow the quenching water into the sewage system.

---

## 06. Accidental release measures

### Personal precautions

Provide for sufficient ventilation. Do not inhale the vapour. Refer to protective measures listed in sections 7 and 8.

### Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP P 605, COMP B (CONIPOX 605)  
605\_B  
**Revision :** 07.07.2006      **Version :** 6.0.0  
**Print date :** 24.07.2006

---

## Methods for cleaning up/collecting

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13). Clean preferably with a detergent; avoid use of solvents. Provide for sufficient ventilation.

---

## 07. Handling and storage

### Information for safe handling

Avoid contact with skin and eyes. Do not inhale the vapour. Do not eat or drink during work - no smoking. Comply with the health and safety at work laws. Provide for fresh air ventilation.

### Requirements to be met by storerooms and containers

Containers should be kept dry and sealed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Information about separation of incompatible products

Keep away from oxidizing agents, from strongly alkaline and strongly acid materials.

### Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.

**Storage class (VCI) :** 8

---

## 08. Exposure controls and personal protection

### Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL (=Occupational Exposure Limit) , suitable respiratory protection must be worn.

### Personal protective equipment

#### Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn. Provide for fresh air ventilation.

#### Hand protection

Butylrubber  $\geq 0,5\text{mm}$   $\geq 480$  min. After washing hands replace lost skin fat by fat containing skin creams. By using other gloves with a lower endurance, change them more often.

#### Eye protection

Use safety glasses.

#### Body protection

Light protective clothing.

---

## 09. Physical and chemical properties

### Image

**Form :** Liquid.  
**Colour :** Colourless.  
**Odour :** Like amine. Ammonia

### Relevant safety data

**Boiling point / range :** ( 1013 hPa ) no data available  
**Flash point :** > 100 °C DIN 53213

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP P 605, COMP B (CONIPOX 605)  
605\_B  
**Revision :** 07.07.2006      **Version :** 6.0.0  
**Print date :** 24.07.2006

---

**Vapour pressure :** ( 50 °C )      no data available  
**Density :** ( 20 °C )      1,01 g/cm<sup>3</sup>  
**Solvent-separation test :** ( 20 °C )      inapplicable  
**Viscosity :** ( 20 °C )      310 mPa.s

---

## 10. Stability and reactivity

### Conditions to avoid

Stable under recommended storage and handling conditions(See section 7).

### Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.  
Exothermic reactions with isocyanates and epoxide resin.

### Hazardous decomposition products

Corrosive gases / vapours. Ammonia When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

---

## 11. Toxicological information

### Experience on practice

Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea. The product causes skin corrosions, and it causes serious damage to eyes.

### Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC). Danger of irritation to eyes, nose, throat and the air passages.

---

## 12. Ecological information

### Details on elimination (persistence / degradability)

#### Biological degradation / elimination

Specification : Biodegradadtion ( 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS-No. : 2855-13-2 )  
Value / dosage : 8 %  
Testing method : EEC C.4-A(DOC)

### Ecotoxic effects

#### Aquatic toxicity

Specification : Toxicity to fish ( BENZYL ALCOHOL ; CAS-No. : 100-51-6 )  
Parameters : LC 50  
Pimephales promelas

Value / dosage : 460 mg/l  
Test-period : 96 h

Specification : Toxicity to fish ( BENZYL ALCOHOL ; CAS-No. : 100-51-6 )  
Parameters : LC 50  
Lepomis macrochirus

Value / dosage : 27 mg/l  
Test-period : 96 h

Specification : Toxicity to daphnia ( BENZYL ALCOHOL ; CAS-No. : 100-51-6 )  
Parameters : EC50  
Species: Daphnia magna Straus 1820

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP P 605, COMP B (CONIPOX 605)  
605\_B  
**Revision :** 07.07.2006      **Version :** 6.0.0  
**Print date :** 24.07.2006

---

Value / dosage : 400 mg/l  
Test-period : 24 h  
Specification : Toxicity to algae ( BENZYL ALCOHOL ; CAS-No. : 100-51-6 )  
Parameters : EC50  
Scenedesmus subspicatus

Value / dosage : 640 mg/l  
Test-period : 96 h  
Specification : Toxicity to fish ( 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS-No. : 2855-13-2 )  
Parameters : LC 50  
Brachydanio rerio

Value / dosage : 70 mg/l  
Test-period : 96 h  
Testing method : EC 84/449  
Specification : Toxicity to daphnia ( 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS-No. : 2855-13-2 )  
Parameters : EC50  
Species: Daphnia magna Straus 1820

Value / dosage : 44 mg/l  
Test-period : 24 h  
Specification : Toxicity to daphnia ( 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS-No. : 2855-13-2 )  
Parameters : NOEC  
Species: Daphnia magna Straus 1820

Value / dosage : 3 mg/l  
Test-period : 504 h  
Testing method : OECD 202 part 2  
Specification : Toxicity to algae ( 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS-No. : 2855-13-2 )  
Parameters : EC50  
Scenedesmus subspicatus

Value / dosage : 37 mg/l  
Test-period : 72 h  
Testing method : EC 88/302  
Specification : Toxicity to algae ( 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS-No. : 2855-13-2 )  
Parameters : NOEC  
Scenedesmus subspicatus

Value / dosage : 1,5 mg/l  
Test-period : 72 h  
Testing method : EC 88/302  
Specification : Toxicity to fish ( 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL ; CAS-No. : 90-72-2 )  
Parameters : LC 50  
Species: Trout

Value / dosage : 222 mg/l  
Test-period : 24 h

**Toxicity to bacteria**  
Specification : Toxicity to bacteria ( 3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS-No. : 2855-13-2 )

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP P 605, COMP B (CONIPOX 605)  
605\_B  
**Revision :** 07.07.2006      **Version :** 6.0.0  
**Print date :** 24.07.2006

---

**Parameters :** EC10  
Pseudomonas putida  
**Value / dosage :** 1120 mg/l  
**Test-period :** 18 h

## Additional ecological information

### General ecological information

Do not empty into waters or drains.

---

## 13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

### Product

#### Waste key

According to the actual waste legislation it is not possible for us to give the waste code because it depends on the application of the product that we do not know here. If you need some help to determine this code, please ask your executives. Disposal Code according to European Waste Catalog (EWC) please specify according to the use of product, e.g.: 080111\* Waste from production, formulation, sales and application of paints and varnishes. Old paints and varnishes, containing organic solvents or some other dangerous product.

---

## 14. Transport information

### Land transport ADR/RID

#### Classification

**Class :** 8      **Kemlercode :** 80  
**Substance number :** 2735      **Classification-Code :** C7

LQ19

#### Proper shipping name

AMINE, LIQUID, CORROSIVE, N.O.S.

#### Hazardous components

M-PHENYLENEBIS(METHYLAMINE)

#### Packaging

**Packaging group :** III  
**Label :** 8

### Maritime transport IMDG/GGVSea

#### Classification

**IMDG-Code :** 8      **EmS number :** F-A / S-B  
**UN number :** 2735      **Marine Poll. :** -

LQ 5 I

#### Proper shipping name

AMINE, LIQUID, CORROSIVE, N.O.S.

#### Hazardous components

M-PHENYLENEBIS(METHYLAMINE)

#### Packaging

**Packaging group :** III  
**Label :** 8

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP P 605, COMP B (CONIPOX 605)  
605\_B  
**Revision :** 07.07.2006      **Version :** 6.0.0  
**Print date :** 24.07.2006

---

## Air transport ICAO-TI and IATA-DGR

### Classification

**Class :** 8  
**UN number :** 2735

### Proper shipping name

AMINE, LIQUID, CORROSIVE, N.O.S.

### Hazardous components

M-PHENYLENEBIS(METHYLAMINE)

### Packaging

**Packaging group :** III  
**Label :** 8

---

## 15. Regulatory information

### Classification according to EC directives

#### Danger symbol and danger designation



C ; Corrosive

#### Hazard-determining components of labelling

M-PHENYLENEBIS(METHYLAMINE) ; CAS-No. : 1477-55-0  
CYCLOHEX-1,2-YLENEDIAMINE ; CAS-No. : 694-83-7  
3-AMINOMETHYL-3,5,5-TRIMETHYLCYCLOHEXYLAMINE ; CAS-No. : 2855-13-2  
POLYOXYPROPYLEN DIAMINE ; CAS-No. : 9046-10-0

#### R-phrases

34 Causes burns.  
43 May cause sensitisation by skin contact.  
20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

#### S-phrases

1/2 Keep locked up and out of the reach of children.  
35 This material and its container must be disposed of in a safe way.  
51 Use only in well-ventilated areas.  
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.  
46 If swallowed, seek medical advice immediately and show this container or label.  
64 If swallowed, rinse mouth with water (only if the person is conscious).  
28 After contact with skin, wash immediately with plenty of ... (to be specified by the manufacturer).  
45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).  
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

### National regulatory information

Germany: Safety Instruction Code of German occupational safety and health organisation. Berufsgenossenschaften der Bauwirtschaft: GISCODE RE 1

#### Regulation on inflammable liquids (VbF)

VbF-Class : Not dangerous according to VbF

#### Emission control act ("TA-Luft")

# Material Safety Data Sheet

according to 91/155/EEC

**Product name :** MASTERTOP P 605, COMP B (CONIPOX 605)  
605\_B  
**Revision :** 07.07.2006      **Version :** 6.0.0  
**Print date :** 24.07.2006

---

Sum organic substances class I : 10 - 15 %

## **Water pollution classification**

Class : 2 according VwVwS

## **Other regulations**

Please refer to guideline M 004 "Irritant/Corrosive Chemicals" BG Chemie! (DE)

---

## **16. Other information**

### **Further information**

We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 16 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

### **Relevant changes**

08. Components with critical values that require monitoring at the workplace (exposure limits) · 14. Land transport ADR/RID and GGVS/GGVE · 14. Classification (ADR) · 14. Proper shipping name (ADR) · 14. Substance releasing the danger (ADR) · 14. Maritime transport IMDG/GGVSea · 14. Classification (IMDG) · 14. Proper shipping name (IMDG) · 14. Substance releasing the danger (IMDG) · 14. Air transport ICAO-TI and IATA-DGR · 14. Proper shipping name (ICAO) · 14. Substance releasing the danger (ICAO) · 15. Hazard-determining components of labelling · 15. R-phrases

### **R-Phrases of components**

20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
20/22	Harmful by inhalation and if swallowed.
21/22	Harmful in contact with skin and if swallowed.
22	Harmful if swallowed.
34	Causes burns.
36/38	Irritating to eyes and skin.
43	May cause sensitisation by skin contact.
52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### **Department issuing data sheet**

BASF Construction Chemicals Business Line Performance Flooring.

### **Contact**

R. Burgos / C. Schmidt

---

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

---