

SAFETY DATA SHEET

MBRACE LAMINATE ADHESIVE HT65 PART A BASE

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY

PRODUCT NAME: MBRACE LAMINATE ADHESIVE HT65 PART A BASE

PART No.: F355636

SUPPLIER: BASF Construction Chemicals
Albany House
Swinton Hall Road
Swinton Manchester M27 4DT

TEL: (+44) 161 794 7411

FAX: (+44) 161 727 8547

2 COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	CONTENTS	HEALTH (class)	RISK (R No.)
REACTION PRODUCT BISPHENOL A	25085-99-8	60-100 %	Xi, N	36/38, 43, 51/53
REACTION PRODUCT BISPHENOL F	28064-14-4	5-10 %	Xi, N	36/38, 43, 51/53
ALKYLGLICIDYLETHER	68081-84-5	5-10 %	Xi, N	36/38, 43, 51/53

COMPOSITION COMMENTS: Two component epoxy resin based product.: Base component based on bisphenol F epoxy resin.

3 HAZARDS IDENTIFICATION

Irritating to eyes and skin.
May cause sensitisation by skin contact.
Toxic to aquatic organisms.
May cause long-term adverse effects in the aquatic environment.

4 FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

INGESTION: DO NOT INDUCE VOMITING! NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS! Rinse mouth thoroughly. Promptly get affected personnel to drink large volumes of water to dilute the swallowed chemical. Obtain medical advice. Provide rest, warmth and fresh air.

SKIN: Important to remove the substance from the skin immediately. Wash the skin immediately with soap and water. Get medical attention promptly if symptoms occur after washing. Chemical burns must be treated by a physician.

EYES: Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

MBRACE LAMINATE ADHESIVE HT65 PART A BASE

5 FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Fire can be extinguished using: Water spray. Powder, foam or CO₂.

6 ACCIDENTAL RELEASE MEASURES

PRECAUTIONS TO PROTECT ENVIRONMENT:

Avoid subsoil penetration. Prevent product from entering drains. Do not contaminate surface water.

SPILL CLEANUP METHODS:

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Wear necessary protective equipment.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS:

Provide sufficient air exchange and/or exhaust in work rooms. Handle and open container with care. Avoid formation of aerosol

STORAGE PRECAUTIONS:

Keep away from food and drink. Keep container tightly closed at room temperature in the original container.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



VENTILATION:

Provide adequate general and local exhaust ventilation.

RESPIRATORS:

In case of insufficient ventilation wear suitable respiratory equipment.

PROTECTIVE GLOVES:

Use protective gloves.

EYE PROTECTION:

Use approved safety goggles or face shield.

HYGIENIC WORK ROUTINES:

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. No eating or drinking while working with this material.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Paste or slurry.	COLOUR:	Grey.
ODOUR/TASTE:	N/A.		
SOLUBILITY DESCRIPTION:	Immiscible with water.	SPECIFIC GRAVITY (Water=1):	1.45
FLASH POINT (°C):	>93(20)		

10 STABILITY AND REACTIVITY

STABILITY:

Normally stable.

CONDITIONS TO AVOID:

Take necessary action to avoid static electricity discharge

MATERIALS TO AVOID:

Strong acids and strong bases strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS:

Burning produces obnoxious and toxic fumes. Carbon Oxides

MBRACE LAMINATE ADHESIVE HT65 PART A BASE

11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL DATA:

Acute toxicity. LD50. Oral. Rat. >5000 mg/kg

SKIN: May cause sensitisation by skin contact.

12 ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL DATA:

Acute toxicity. LC50 96 hours fish 2.4mg/l
Acute toxicity. LC50 96 hours Daphnia 3.6mg/l

ENVIRONMENTAL HAZARDS: Avoid subsoil penetration. Do not let product enter drains. Do not contaminate surface water.


DEGRADABILITY: Not really Biodegradeable

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS: Dispose of in accordance with Local Authority requirements.

14 TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



ROAD:

UN No: 3082
HAZARD CLASS (ADR): Class 9: Miscellaneous dangerous substances and articles.
ADR CLASS No: 9 **ADR ITEM No:** 11 (c)
PROPER SHIPPING NAME I: ENVIROMENTALLY HAZARDOUS SUBSTANCE, LIQUID, NOS (Contains Epoxy Resin)

RAIL:

RAIL TRANSPORT CLASS No: 9 **RAILROAD PT:** 11 (c)

SEA:

SEA TRANSPORT CLASS No: Not Regulated

AIR:

AIR TRANSPORT CLASS No: Not Regulated

MBRACE LAMINATE ADHESIVE HT65 PART A BASE

15 REGULATORY INFORMATION

LABEL FOR SUPPLY:



IRRITANT



DANGEROUS FOR
THE ENVIRONMENT

RISK PHRASES:	R-36/38 R-43	Irritating to eyes and skin. May cause sensitisation by skin contact.
SAFETY PHRASES:	S-26 S-37 S-24/25 P-5 S-60	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves. Avoid contact with skin and eyes. Contains epoxy constituents. See information supplied by the manufacturer. This material and its container must be disposed of as hazardous waste.
GUIDANCE NOTES:	Occupational Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).	

16 OTHER INFORMATION

REVISION DATE:	01/10/01
REVISION No. /REPLACES SDS ISSUED:	Issue 1
SDS No.:	SDS0202