


**THOROSEAL FX100 PART 1**

Irritant

**1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**

Product Name	THOROSEAL® FX100 PART 1
Recommended use	Waterproofing agent
Manufacturer / Distributor	BASF Construction Chemicals UK Ltd Albany House, Swinton Hall Road, Swinton, Manchester, M27 4DT Tel: +44 161 794 7411 - Fax: +44 161 727 8547 Website: www.basf-cc.co.uk
Emergency information	UK : Tel: + 44 161 794 7411

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical characteristics	Modified cementitious mortar
Hazardous components	
Portland cement (Cr-VI < or = 2 ppm)	Conc: 20 - 70 % - Einecs: 266-043-4 - CAS: 65997-15-1 - Xi - R36/37/38, R41

**3. HAZARDS IDENTIFICATION**

Risks	R36/37/38 - Irritating to eyes, respiratory system and skin. R41 - Risk of serious damage to eyes.
-------	---

**4. FIRST AID MEASURES**

Eye contact	Flush with water for at least 15 minutes. Get medical attention.
Skin contact	Remove and wash contaminated clothes. Wash affected area with soap and plenty of water. Get medical attention if irritation persists.
Inhalation	Remove affected person to fresh air. In case of breathing difficulty or distress, get medical attention.
Ingestion	If accidentally swallowed drink plenty of water and obtain medical attention. Point out the high alkalinity of cement.

**5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	Foam, water mist, carbon dioxide, dry powder
Extinguishing media which must not be used for safety reasons	Water jet
Special exposure hazards arising from the substance or preparation itself, its combustion products, or released gases	None
Protective equipment	Wear self-contained breathing apparatus and protective suit.

**6. ACCIDENTAL RELEASE MEASURES**

Personal precautions	Avoid contact with skin and eyes.
----------------------	-----------------------------------

---

**THOROSEAL FX100 PART 1**

---

Environmental precautions

Do not discharge into drains and sewers because of high alkalinity.

Methods for cleaning up

Collect mechanically and dispose as per 13.

Avoid formation of dust.

**7. HANDLING AND STORAGE**

Handling

Avoid dust formation.

Do not inhale dust.

Storage

Store away from wet and humid areas.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

Exposure limits values

not applicable

Exposure controls :

Occupational exposure controls

not applicable

Environmental exposure controls

not applicable

Personel protection :

Do not eat, drink or smoke at workplace.

Store separate from food and food containers.

Respiratory protection

dust mask (filter St)

Hand protection

protective gloves

Eye protection

goggles

Skin and body protection

tightly closed work clothes

Wash hands before breaks and after finishing work.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Form

powder

Colour

grey

Odour

odourless

Density

not applicable

Bulk density

not applicable

pH

&gt; 11 at 20 °C

Flash point

not applicable

Autoignition temperature

not applicable

Vapour pressure

not applicable

Water solubility

miscible

Viscosity

not applicable

Explosion limits :

- upper

not applicable

- lower

not applicable

Decomposition temperature

not applicable

Boiling point/range

not applicable

Other data

low Chromate - Cr-VI &lt; 2 ppm

Mixing with water results in an alkaline suspension. Simultaneous hardening with emission of hydration heat occurs.

**10. STABILITY AND REACTIVITY**

Conditions to avoid

None known

Materials to avoid

None known

---

**THOROSEAL FX100 PART 1**

---

Hazardous decomposition products

None, under application conditions.

**11. TOXICOLOGICAL INFORMATION**

Acute toxicity :

LD50 oral rat

not determined

LD50 dermal rat

not determined

LD50 dermal rabbit

not determined

LC50 inhalation rat

not determined

Acute effects/symptoms :

Cement and mortar dust irritate eyes and, by prolonged contact, the skin. Mixing with water results in an alkaline suspension that has an irritant effect on eyes and skin.

After eye contact

Irritating to eyes.

After skin contact

Irritating to skin.

After inhalation

Inhalation of cement dust may cause irritation of the respiratory tracts.

After ingestion

not determined

Chronic effects

May cause sensitisation by inhalation and skin contact.

**12. ECOLOGICAL INFORMATION**

Ecotoxicity effects

Do not discharge into drains and sewers because of high alkalinity. Due to its alkalinity, this product is harmful to fish and other aquatic life forms.

Discharge only after neutralisation.

**13. DISPOSAL CONSIDERATIONS**

Product

Re-use where possible. Dispose according to local regulations for construction materials.

Packaging

Dispose according to local regulations.

**14. TRANSPORT INFORMATION**

General

This product is not classified as dangerous in the meaning of transport regulations.

Road transport - ADR

Railway transport - RID

Sea transport - IMDG

Air transport - ICAO/IATA

**15. REGULATORY INFORMATION**

Labelling

Xi - Irritant

R-phrase(s)

R36/37/38 - Irritating to eyes, respiratory system and skin.

R41 - Risk of serious damage to eyes.

S-phrase(s)

S 2 - Keep out of reach of children.

S22 - Do not breathe dust.

S24/25 - Avoid contact with skin and eyes.

S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S36/37/39 - Wear suitable protective clothing, gloves, and eye/face protection.

S46 - If swallowed, seek medical advice immediately and show this container or label.

---

**THOROSEAL FX100 PART 1**

---

**16. OTHER INFORMATION**

Further information

None

Relevant changes

R-phrases of components

R36/37/38 - Irritating to eyes, respiratory system and skin.

R41 - Risk of serious damage to eyes.

Important Note

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

---

---