

Material Safety Data Sheet

according to 91/155/EEC

Product name : UCRETE PART 3 PRIMER SC
Revision : 10.10.2006 **Version :** 4.0.0
Print date : 12.10.2006

01. Identification of substance, preparation and company

Product name

UCRETE PART 3 PRIMER SC (F199554)
(FOR PRIMER SC, PRIMER SCF)

Manufacturer/Supplier

BASF Construction Chemicals (UK) Ltd.

Street/P.O.Box

19 Broad Ground Road Lakeside Industrial Estate /

Country code/Postal code/Town/City

B 98 8YP Redditch, Worcestershire

Telephone / Telefax

+44(0)161 794 7411 / +44(0)161 727 8547

Emergency information

Schweizer Toxzentrum +0041-1-2515151 (CH)
Centre Anti - Poison +0033 01 40 37 04 04 (FR)
Toxikologické informa-ní st-edisko +00420 224 919 293 (CZ)
Myrkytystietokeskus puh.(suora) +358 (0) 9 471 977 (vaihde) 094711 (FIN)

02. Composition/information on ingredients

Chemical characterization

Mineral Fillers

Hazardous components

CALCIUM HYDROXIDE ; EC-No. : 215-137-3 ; CAS-No. : 1305-62-0

Percentage : 50 - 100 %

Classification : Xi ; R 41 Xi ; R 38

For the wording of the listed risk phrases refer to section 16.

03. Hazards identification

Hazard designation

Risk of serious damage to eyes.

Classification : Xi ; R 41 · Xi ; R 38

04. First-aid measures

After inhalation

Take the casualty into the fresh air and keep warm. Call a doctor, should the air passages be affected.

After skin contact

The product causes skin corrosions, and it causes serious damage to eyes. Immediately remove all contaminated clothing. Flush with plenty of water.

After eye contact

The product causes skin corrosions, and it causes serious damage to eyes. Remove contact lenses, keep eyelids open. Flush with plenty of water (10 - 15 min.). Call a physician. After first aid treatment immediately seek medical advice.

After ingestion

Contact a doctor immediately. Keep at rest. Do not induce vomiting.

Material Safety Data Sheet

according to 91/155/EEC

Product name : UCRETE PART 3 PRIMER SC
Revision : 10.10.2006 **Version :** 4.0.0
Print date : 12.10.2006

05. Fire-fighting measures

Suitable extinguishing media

Not combustible under normal conditions.

Unsuitable extinguishing media

Waterjet.

Special protective equipment

Appropriate breathing apparatus may be required.

Additional information

Do not allow the quenching water into the sewage system.

06. Accidental release measures

Personal precautions

Provide for sufficient ventilation. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not empty into drains. If the product contaminates lakes, rivers or sewages, inform appropriate authorities in accordance with local regulations.

07. Handling and storage

Information for safe handling

Do not eat or drink during work - no smoking. Comply with the health and safety at work laws.

Requirements to be met by storerooms and containers

Containers should be kept dry and sealed. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information about storage conditions

Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight.

Storage class (VCI) : 13

08. Exposure controls and personal protection

Additional information about engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates below the OEL (=Occupational Exposure Limit), suitable respiratory protection must be worn.

Components with critical values that require monitoring at the workplace (exposure limits)

CALCIUM HYDROXIDE ; CAS-No. : 1305-62-0

Specification : TLV/TWA (GB)

Value : 5 mg/m³ / 8 h

Version date :

Personal protective equipment

General protective and hygiene measures

Wash hands before breaks and after work.

Material Safety Data Sheet

according to 91/155/EEC

Product name : UCRETE PART 3 PRIMER SC
Revision : 10.10.2006 **Version :** 4.0.0
Print date : 12.10.2006

Respiratory protection

If workplace limits are exceeded, a gas mask approved for this purpose must be worn.

Hand protection

Use protective gloves. After washing hands replace lost skin fat by fat containing skin creams.

Eye protection

Use safety glasses.

Body protection

Personel should wear protective clothings and all parts of the body should be washed after contact. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at neck and wrists through contact with the powder is avoided.

09. Physical and chemical properties

Image

Form : Powder.
Colour : White.
Odour : Poor, characteristic.

Relevant safety data

| | | | |
|--------------------------------------|-----------|----------------|-------------------|
| Physical state : | | solid | |
| Melting point / range : | > | 580 | °C |
| Decomposition point / range : | | 550 - 600 | °C |
| Flash point : | | not applicable | DIN 53213 |
| Vapour pressure : | (50 °C) | inapplicable | |
| Density : | (20 °C) | 2,3 | g/cm ³ |
| Solvent-separation test : | (20 °C) | inapplicable | |

10. Stability and reactivity

Conditions to avoid

Stable under recommended storage and handling conditions(See section 7). Protect against moisture and water.

Materials to avoid

Reactions with acids: development of heat.

11. Toxicological information

Experience on practice

The product causes skin corrosions, and it causes serious damage to eyes.

Additional toxicological information

The product was classified in toxicological terms on the basis of the results of the calculation procedure outlined within General Directive on Preparations (1999/45/EC).

12. Ecological information

Additional ecological information

General ecological information

Do not empty into waters or drains.

Material Safety Data Sheet

according to 91/155/EEC

Product name : UCRETE PART 3 PRIMER SC
Revision : 10.10.2006 **Version :** 4.0.0
Print date : 12.10.2006

13. Disposal considerations

Contaminated packaging must be emptied of all residues and, following appropriate cleaning, may be sent to a recycling plant. Uncleaned packaging must be disposed of in the same manner as the medium.

Product

Waste key

According to the actual waste legislation it is not possible for us to give the waste code because it depends on the application of the product that we do not know here. If you need some help to determine this code, please ask your executives. Other construction and demolition wastes (including mixed wastes) containing dangerous substances.

14. Transport information

Land transport ADR/RID

Classification

Class : -

Maritime transport IMDG/GGVSea

Classification

IMDG-Code : -

Air transport ICAO-TI and IATA-DGR

Classification

Class : -

15. Regulatory information

Classification according to EC directives

Danger symbol and danger designation



Xi ; Irritant

R-phrases

41 Risk of serious damage to eyes.
38 Irritating to skin.

S-phrases

2 Keep out of the reach of children.
35 This material and its container must be disposed of in a safe way.
39 Wear eye/face protection.
46 If swallowed, seek medical advice immediately and show this container or label.
64 If swallowed, rinse mouth with water (only if the person is conscious).
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
24/25 Avoid contact with skin and eyes.

National regulatory information

Regulation on inflammable liquids (VbF)

VbF-Class : Not dangerous according to VbF

Water pollution classification

Class : 1 according VwVwS

Material Safety Data Sheet

according to 91/155/EEC

Product name : UCRETE PART 3 PRIMER SC
Revision : 10.10.2006 **Version :** 4.0.0
Print date : 12.10.2006

16. Other information

Further information

We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 16 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

Relevant changes

15. R-phrases · 15. S-phrases

R-Phrases of components

38 Irritating to skin.
41 Risk of serious damage to eyes.

Department issuing data sheet

BASF Construction Chemicals Business Line Performance Flooring.

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
